

MODULAR PARTITION
SYSTEM MOD92

MOD92 SLIDING DOOR DOUBLE-LEAF

Double-leaf aluminium profile doors with glass opening
In the top rail of the door leaf,
there are stops for fixing the open and closed positions



WIDTH (W)*

M7 (700 mm) - M13 (1300 mm)
+ M7 (700 mm) - M13 (1300 mm)

HEIGHT (H)*

M15 (1500 mm) – M25 (2500 mm)

PROFILE CROSS-SECTION

75 x 30 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm
Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal
and vertical surfaces $m \pm 3$ mm per 2000mm

EXTRAS

Glass tinting

*Dimensions depend on the door weight (max 80 kg + 80 kg)
Custom solutions upon agreement

PROFILE MATERIAL

Aluminium

FINISH FOR PROFILES

Natural anodisation, paint (RAL)

THRESHOLD

None

SEALS

None

RAIL SYSTEM

Top rail with a load capacity of 80 kg + 80 kg,
with a floor guide

HANDLE

Pull handle, recessed handle

LOCK CASE

None, LC306, AGB 702

VARIOUS GLASS TYPES AVAILABLE

6 mm / 8 mm tempered
44.1 laminated

