

MODULAR PARTITION
SYSTEM MOD92

MOD92 SOUNDPROOF SLIDING DOOR SINGLE-LEAF

Aluminium profile door with glass opening, perimeter sealed
In the top rail of the door leaf,
there are stops for fixing the open and closed positions



WIDTH (W)*

M7 (700 mm) - M15 (1500 mm)

HEIGHT (H)*

M21 (2100 mm)

PROFILE CROSS-SECTION

75 x 30 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm
Deviation tolerance = +10...-8

NB! The largest allowed deviation of the upper
horizontal and vertical surfaces +/-3mm per 2000mm

The largest allowed deviation of the bottom
horizontal surfaces +/-1mm per 2000mm

EXTRAS

Glass tinting

*Dimensions depend on the door weight (max 80 kg)

**Alternative glass options available upon mutual agreement
Custom solutions upon agreement

PROFILE MATERIAL

Aluminium

FINISH FOR PROFILES

Natural anodisation, paint (RAL)

THRESHOLD

Aluminium shining 40 x 5 mm

SEALS

Black

RAIL SYSTEM

Top rail with a load capacity of 80 kg,
with a floor guide

HANDLE

Pull handle

LOCK CASE

None, LC306, AGB 702

VARIOUS GLASS TYPES AVAILABLE**

44.2 SC = Rw 34 dB
(Report No VTT-S-02285-17)

