

TK MODULAR PARTITION SYSTEM

TK SLIDING DOOR SINGLE-LEAF

All-glass sliding door with no frame
Door attaches to the ceiling / top glass via a top rail
In the rail, there are stops for fixing
the open and closed positions
Details assembled on site



LAIUS (L) * / **

M7 (700 mm) - M13 (1300 mm)

KÖRGUS (H) * / **

M15 (1500 mm) – M25 (2500 mm)

UKSE LEHT

Tempered glass 10-12 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size

Deviation tolerance = +5...-1

Opening Width (L) = product size

Deviation tolerance = +6...-2

NB! The largest allowed deviation of the horizontal
and vertical surfaces m+/-3mm per 2000mm

THRESHOLD

None

RAIL SYSTEM

Top rail with a load capacity of 80 kg,
with a floor guide

RAIL SYSTEM FINISH

Natural anode, paint (RAL)

PULL HANDLES

According to the design

LOCK CASE**

Floor lock

VARIOUS GLASS TYPES AVAILABLE

Laminated, tinted glass

EXTRAS

Film coating

*Dimensions depend on the door weight (max 80 kg)

**Custom solutions upon agreement

