

TK MODULAR PARTITION SYSTEM

TKU SLIM HINGED DOOR DOUBLE-LEAF

All-glass door with aluminium frame and door frame



WIDTH (W)*

M7 (690 mm) - M10 (1090 mm)
+ M3 (300 mm) - M9 (900 mm)

DOOR LEAF

Tempered glass 10 - 16 mm

HEIGHT (H)*

M21 (2090 mm) – M26 (2590 mm)

NOTES

The maximum width/height of the door depends on the thickness of the glass, see table

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm
Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal and vertical surfaces m+/-3mm per 2000mm

FRAME FINISH

Natural anodisation, paint (RAL)

THRESHOLD

None, aluminium, drop-down seal

HINGES

Concealed hinges

LOCK CASE WITH A LEVER**

LC190 (lockable) / LC290 (not lockable) /
VALNES E114 / ASSA 565

VARIOUS GLASS TYPES AVAILABLE

10 mm = Rw 33 - 35 dB

12 mm = Rw 36 dB

55.2 SC = Rw 38 dB

66.2 SC = Rw 39 dB

88.2 SC = Rw 40 dB

EXTRAS

Film coating, tinted glass, door closer

* Custom dimensions upon agreement

** Upon agreement: electric striking plate/ electric motorlock

PRODUCT TYPES

	M21			M22 - M23			M24 - M26		
	10mm/55.2sc	12mm/66.2sc	88.2sc	10mm/55.2sc	12mm/66.2sc	88.2sc	10mm/55.2sc	12mm/66.2sc	88.2sc
M7 - M8	OK	OK	OK	OK	OK	OK	OK	OK	-
M9	OK	OK	OK	OK	OK	OK	OK	OK	-
M10	OK	OK	OK	OK	OK	-	OK	-	-

