

TK MODULAR PARTITION SYSTEM

TKU SLIM HINGED DOOR SINGLE-LEAF

All-glass door with aluminium frame and door frame



WIDTH (W)*

M7 (690 mm) - M11 (1090 mm)

DOOR LEAF

Tempered glass 10 - 16 mm

HEIGHT (H)*

M21 (2090 mm) – M26 (2590 mm)

NOTES

The maximum width/height of the door depends on the thickness of the glass, see table

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm
Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal and vertical surfaces m+/-3mm per 2000mm

FRAME FINISH

Natural anodisation, paint (RAL)

THRESHOLD

None, aluminium, drop-down seal

HINGES

Concealed hinges

LOCK CASE WITH A LEVER**

LC190 (lockable) / LC290 (not lockable) /
VALNES E114 / ASSA 565

VARIOUS GLASS TYPES AVAILABLE

10 mm = Rw 33 - 35 dB
12 mm = Rw 36 dB
55.2 SC = Rw 38 dB
66.2 SC = Rw 39 dB
88.2 SC = Rw 40 dB

EXTRAS

Film coating, tinted glass, door closer

* Custom dimensions upon agreement

** Upon agreement: electric striking plate/ electric motorlock

