

VAL MODULAR PARTITION SYSTEM

# VAL BEVELLED EDGE DOOR DOUBLE-LEAF

With solid wood frame and fibreboard covered door leaf with a bevelled edge, available blind or with glass opening  
Finger-jointed glue-laminated timber frame  
Consists of an active door leaf and an inactive door leaf



WIDTH (W)\*

M7 (690 mm) - M10 (990 mm)  
+ M3 (300 mm) – M9 (900 mm)

HEIGHT (H)\*

M21 (2090 mm) – M24 (2390 mm)

DEPTH\*

92 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm  
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm  
Deviation tolerance = +10...-8

**NB!** The largest allowed deviation of the horizontal and vertical surfaces m+/-3mm per 2000mm

Product types

Type	WM2-27	WM2-39	WM2-42
Sound insulation index (Rw)	-	39 dB	42 dB
Glass used in glass opening (Rw)	6 (30 dB)	44.2 SC (37 dB)	66.2 SC (40 dB)

FINISH

Paint, veneer, varnish, stain, HPL (laminate)

THRESHOLD

None, oak, drop-down seal

HINGES

Leaf hinge

LOCK CASE\*\*

LC190 (lockable), LC290 (not lockable),  
EL580 (electrically lockable)

EXTRAS

Kickplate, concealed hinges

\*Custom dimensions upon agreement

\*\*Custom solutions upon agreement



