

VAL MODULAR PARTITION SYSTEM

VAL BEVELLED EDGE DOOR SINGLE-LEAF

With solid wood frame and fibreboard covered door leaf with a bevelled edge, available blind or with glass opening
Finger-jointed glue-laminated timber frame



WIDTH (W)*

M7 (690 mm) - M10 (990 mm)

HEIGHT (H)*

M21 (2090 mm) – M24 (2390 mm)

DEPTH*

92 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm

Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm

Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal and vertical surfaces m+/-3mm per 2000mm

FINISH

Paint, veneer, varnish, stain, HPL (laminate)

THRESHOLD

None, oak, drop-down seal

HINGES

Leaf hinge

LOCK CASE**

LC190 (lockable), LC290 (not lockable),
EL580 (electrically lockable)

Product types

Type	WM1-27	WM1-39	WM1-42
Sound insulation index (Rw)	-	39 dB	42 dB
Glass used in glass opening (Rw)	6 (30 dB)	44.2 SC (37 dB)	66.2 SC (40 dB)

EXTRAS

Kickplate, concealed hinges

*Custom dimensions upon agreement

**Custom solutions upon agreement



