

VAL MODULAR PARTITION SYSTEM

VAL MODULE

Frame consisting of profiles,
which contains various fillers fixed with seals.



WIDTH (W)*

150 - 1400 mm

HEIGHT (H)*

240 - 2750 mm

DEPTH

92 mm

PROFILE THICKNESS**

30 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm
Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm
Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal
and vertical surfaces m+/-3mm per 2000mm

PROFILE MATERIAL

MDF, plywood, solid wood

FINISH FOR PROFILES

Paint, veneer, varnish, stain

FILLING MATERIAL OPTIONS

Glass, MDF

PROFILE SEAL FINISH

Black

VARIOUS GLASS TYPES AVAILABLE

6 mm = Rw 30 dB
10 mm = Rw 33 - 35 dB
44.2 SC = Rw 37 dB
6.2 SC = Rw 40 dB
108.2 SC = Rw 42 dB
Special glass

EXTRAS

Venetian blinds, tinting, smart glass

*Maximum area of one module 3 m²

**For solid wood profile 42 mm

Option of being used as a top module

The opening, filled with two modules, has a maximum height of 4500 mm

*Custom dimensions upon agreement

