

VAL MODULAR PARTITION SYSTEM

VAL SLIDING DOOR SINGLE-LEAF

Sliding door with MDF profiles with glass opening The top rail of the door leaf has stoppers to fix it in the open and closed positions



WIDTH (W)*

M7 (700 mm) - M13 (1300 mm)

HEIGHT (H)*

M15 (1500 mm) – M25 (2500 mm)

PROFILE CROSS-SECTION

92 x 30 mm

CONDITIONS FOR INSTALLATION OPENING'S MEASUREMENTS

Opening height (H) = product size +10mm Deviation tolerance = +5...-4

Opening Width (L) = product size +20mm Deviation tolerance = +10...-8

NB! The largest allowed deviation of the horizontal and vertical surfaces m+/-3mm per 2000mm

FINISH

Paint, veneer, varnish, stain

THRESHOLD

None

SEALS

None

RAIL SYSTEM

Top rail with a load capacity of 80 kg, with a floor guide

HANDLE

Pull handle, recessed handle

LOCK CASE

None, LC306, AGB 702

VARIOUS GLASS TYPES AVAILABLE

6 mm I 8 mm tempered 44.1 laminated

EXTRAS

Glass tinting

*Dimensions depend on the door weight (max 80 kg) Custom solutions upon agreement

Warreulnw I H1 H2 139