

TEISELDATAV MOODULVAHESEINA SÜSTEEM ALATAR

ALATAR EKSTSENTRILINE PÕRANDASIINIGA

Voldikseinad on põrandasiiniga ning koosnevad seinapaneelidest, mis on omavahel ühendatud hingedega ning mille ladustamine seina avanemisel toimub siini otsas
Kanderullik on paneeli ühes ääres
Paneelide, lae ja põranda vahel on heliisolatsiooni tihendid
Seina eri paneelid on omavahel ühendatud hingedega
Voldikseina iga paneel on varustatud süvistatud sulguriga, mille abil lukustatakse sein eraldi käepidet/linki kasutades

PANEELIDE LAIUS

Max 850 mm

SÜGAVUS

92 mm



PROFIILIDE MATERJAL

Alumiinium

SIINI- JA PIIRDEPROFIILIDE VIIMISTLUS*

RAL9010

PANEELIDE SERVAPROFIILIDE VIIMISTLUS*

Naturaalne anood

PANEELIDE TÄITEMATERJAL*

Valge melamiin (standard), värvitud melamiin (RAL, Tikkurila, NCS kataloogid), dekooriga melamiin, naturaalne spoon, kõrgsurvelaminaat (HPL)

LUKUKORPUS**

Rull-lukk (DIN südamikuga)

KÄEPIDE

Süvistatud

HELIISOLATSIOON***

Rw = 45 dB (30 kg/m²)

Rw = 49 dB (55 kg/m²)

***Oletuslik helipidavus

LISAD

Paneelid klaasiavadega, magnettahvel, koolitahvel

*Eriviimistlused vastavalt kokkuleppele

**Eriühendused vastavalt kokkuleppele

Gabariitmõõdud ühepoolne

Paneeli arv	2,5	4,5	6,5	8,5
laius (mm)	1500 - 2350	2300 - 4200	3500 - 6000	4500 - 7500
kõrgus (mm)	2090-3500****			


Gabariitmõõdud kahepoolne

Paneeli arv	2,5 + 2,5	4,5 + 4,5	6,5 + 6,5	8,5 + 8,5
laius (mm)	3000 - 4600	4500 - 8300	6800 - 11800	9000 - 15000
kõrgus (mm)	2090-3500****			



****Ava kõrgusest sõltub mooduli lubatav laius:
2090-2800mm -max 850mm
2801-3200mm -max 800mm
3201-3500mm -max 750mm

ALATAR eccentric floor track 6.5 panels

Rw=45dB (30kg/m2) / Rw=49dB (55kg/m2)







- × -backside spingalet to floor
- -frontside spingalet to ceiling
- -frontside spingalet to floor
- * -Glass module; available on request



- × -backside spingalet to floor
- -frontside spingalet to ceiling
- -frontside spingalet to floor
- * -Glass module; available on request

ALATAR eccentric floor track 2.5 panels


Rw=45dB (30kg/m2) / Rw=49dB (55kg/m2)



- × -backside spingalet to floor
- -frontside spingalet to ceiling
- -frontside spingalet to floor
- * -Glass module; available on request

ALATAR eccentric floor track 4.5 panels




Rw=45dB (30kg/m2) / Rw=49dB (55kg/m2)



- X -backside spingalet to floor
- O -frontside spingalet to ceiling
- -frontside spingalet to floor
- * -Glass module; available on request

ALATAR eccentric floor track 8.5 panels




Rw=45dB (30kg/m2) / Rw=49dB (55kg/m2)



- × -backside spingalet to floor
- -frontside spingalet to ceiling
- ⊗ -frontside spingalet to floor
- * -Glass module, available on request

ALATAR eccentric floor track 2.5+2.5 panels


Rw=45dB (30kg/m2) / Rw=49dB (55kg/m2)





- × -backside spingalet to floor
- -frontside spingalet to ceiling
- -frontside spingalet to floor
- * -Glass module; available on request

ALATAR eccentric floor track 4.5+4.5 panels

Rw=45dB (30kg/m²) / Rw=49dB (55kg/m²)



- × -backside spingalet to floor
- -frontside spingalet to ceiling
- ◊ -frontside spingalet to floor
- * -Glass module, available on request

$$R_w=45\text{dB (30kg/m}^2\text{)} / R_w=49\text{dB (55kg/m}^2\text{)}$$


- ✕ -backside spingalet to floor
- -frontside spingalet to ceiling
- ⊗ -frontside spingalet to floor
- * -Glass module; available on request